

ENVIRONMENTAL PRODUCT DECLARATION

In accordance with ISO 14025:2006 and EN 15804:2012+A2:2019/AC:2021 for:

MAPEGROUT TISSOTROPICO ZERO

Greek production

An EPD should provide current information and may be updated if conditions change.
The stated validity is, therefore, subject to the continued registration and publication at www.environdec.com.

Programme:	Programme operator:	EPD registration number:	Publication date:	Valid until:	Geographical scope:
The International EPD® System; www.environdec.com	**EPD International AB**	**EPD-IES-0015136**	**2024-11-27**	**2029-11-26**	**Europe**


1 COMPANY DESCRIPTION / GOAL & SCOPE

Founded in 1937 in Milan, Italy, Mapei produces adhesives and complementary products for laying all types of floor, wall and coating materials, and also specializes in other chemical products used in the building industry, such as waterproofing products, specialty mortars, admixtures for concrete, cement additives, products for underground constructions and for the restoration of concrete and historical buildings.
There are currently 96 subsidiaries in the Mapei Group, with a total of 93 production facilities located around the world in 36 different countries and in 5 different continents. Mapei also has 32 central laboratories. Most locations are ISO 9001 and ISO 14001. Mapei invests 12% in its company's total workforce and 5% of its turnover in Research & Development; in particular, 70% of its R&D efforts are directed to develop eco-sustainable and environmentally friendly products, which give important contribution to all major green rating systems for eco-sustainable buildings such as LEED and BREEAM.

Furthermore, Mapei has developed a sales and technical service network with offices all over the world and offers an efficient Technical Assistance Service that is valued by architects, engineers, contractors and owners.

The goal of the study is to provide necessary data and documentation to produce an EPD according to the requirements of PCR Environdec (Version 1.3.4, 2024-04-30) under EN 15804:2012+A2:2019/AC:2021 and to have more comprehension about the environmental impacts related to **Mapegrout Tissotropico Zero** is manufactured in Mapei Hellas S.A. located in Ritsona (Greece), including packaging of the finished products.

Target audiences of the study are customers and other parties with an interest in the environmental impacts **Mapegrout Tissotropico Zero**. This analysis shall not support comparative assertions intended to be disclosed to the public.



MAPEI

EPD®
THE INTERNATIONAL EPD® SYSTEM

2 PRODUCT DESCRIPTION

Mapegrout Tissotropico Zero is a ready-mixed powdered mortar composed of high-strength cements, selected aggregates, special additives and synthetic fibres prepared according to a formula developed in the MAPEI Research & Development laboratories.

Mapegrout Tissotropico Zero is available in 25 kg multiply bag.

UN CPC Code: 375 - Articles of concrete, cement and plaster

For more information see the TDS (Technical Data Sheet) on Mapei SpA website (www.mapei.com).

3 CONTENT DECLARATION

The main components and ancillary materials of the products included in this EPD are the following:

Table 1: Composition referred to 1 kg of product packaged.

Materials	Percentage (%) by mass	Post-consumer recycled material weight-% of product	Biogenic Material, weight-% of product	Biogenic Material, kgC/product or declared unit
Inorganic Binders	< 45% (3,5% recycled pre-consumer)	0	0	0
Organic Binders	< 1%	0	0	0
Filler	< 60%	0	0	0
Additives	< 2%	0	0	0
Packaging Materials	**Weight-% (versus the product)**		**Biogenic Material, kgC/product or declared unit**	
LDPE	< 0,1%		0	
Wood	< 1%		0,00331	
Paper	< 0,5%		0,0015	

The product does not contain a concentration higher than 0,1% (by unit weight) of either carcinogenic substances or substances of very high concern (SVHC) on the REACH Candidate List published by the European Chemicals Agency.

4 DECLARED UNIT AND REFERENCE SERVICE LIFE

The declared unit is 1 kg of product plus the weight of the packaging.

Due to the selected system boundary, the reference service life of the products is not specified.

5 SYSTEM BOUNDARIES AND ADDITIONAL TECHNICAL INFORMATION

The approach is “cradle to gate” (A1–A3) with modules C1-C4 and module D and optional modules (A1-A3 + A4-A5 +C + D):

- **A1, A2, A3** (Product stage): extraction and processing of raw materials (A1), transportation up to the factory gate (A2), manufacturing of the finished product and packaging (A3).
- **A4 – A5** (Construction process stage): transport distance of the finished product to final customers is assumed to be 1000km (A4). The installation phase (A5) includes the electricity consumption for the mixing and the application. The packaging is collected and sent to treatment.
- **C1, C2, C3, C4** (End of Life stage): the demolition phase (C1) includes the electricity for demolition. With a collection rate of 100% as C&D waste, the transports are carried out by lorry over 100 km (C2). A recycling ratio (C3) of 70% is considered in accordance with the European Directive 2008/98/CE. The remaining 30% is landfilled (C4).
- **D** (Resource recovery stage): contains credits from the recycling of the fraction of product in module C3, at the end of life, the product can be collected and recycled for use in substitution of virgin raw aggregates. This module also contains the credit from the incineration of a fraction of packaging waste (A5).

Table 2: System boundaries

	Product stage			Construction process stage		Use stage							End of life stage				Resource recovery stage
	Raw material supply	Transport	Manufacturing	Transport	Construction installation	Use	Maintenance	Repair	Replacement	Refurbishment	Operational energy use	Operational water use	De-construction demolition	Transport	Waste processing	Disposal	Reuse-Recovery-Recycling-potential
Module	**A1**	**A2**	**A3**	**A4**	**A5**	**B1**	**B2**	**B3**	**B4**	**B5**	**B6**	**B7**	**C1**	**C2**	**C3**	**C4**	**D**
Modules declared	X	X	X	X	X	MND	MND	MND	MND	MND	MND	MND	X	X	X	X	X
Geography	GR, EU	GR, EU	GR	EU	EU	-	-	-	-	-	-	-	EU	EU	EU	EU	EU
Specific data	9,3%			-		-	-	-	-	-	-	-	-	-	-	-	-
Variation – products	0%			-		-	-	-	-	-	-	-	-	-	-	-	-
Variation – sites	0%			-		-	-	-	-	-	-	-	-	-	-	-	-

MND: Module Not Declared

A brief description of production process is the following:

The production process starts from raw materials, that are purchased from external and intercompany suppliers and stored in the plant. Bulk raw materials are stored in specific silos and added automatically in the production mixer, according to the formula of the product. Other raw materials, supplied in bags, big bags or tanks, are stored in the warehouse and added automatically or manually in the mixer. The production is a discontinuous process, in which all the components are mechanically mixed in batches. The semi-finished product is then packaged, put on wooden pallets and stored in the finished products warehouse. The quality of final products is controlled before the sale.

Table 3: Transport to the building site (A4)

Scenario information	Value	Unit
Means of transport: truck-trailer euro 5, gross weight 34-40 t, payload capacity 27 t		
Litres of fuel (diesel for truck)	0,0166	l/100km
Transport distance - truck	1000	km
Capacity utilisation (including empty runs) - truck	85	%
Gross density of products transported	~ 1400	kg/m^3
Capacity utilisation volume factor	1	-

Table 4: Installation into the building site (A5)

Scenario information	Value	Unit
Ancillary materials for installation	0	kg
Water use	0,00016	m^3
Other resources use	0	kg/m^2
Electricity and other energy consumption for the installation	0,000159	kWh
Waste materials on building site before waste processing, generated by the product's installation (specified by type)	0,00048 (LDPE) 0,0072 (Wood) 0,00348 (Paper) 0,0104 (C&D waste)	kg
Output materials (specified by type) as result of waste processing at the building site e.g. of collection for recycling, for energy recovery, disposal (specified by route)	0,00407 (Incineration) 0,0104 (Landfill) 0,00706 (Recycling)	kg

Table 5: End of Life (C1-C4)

Scenario information	Value	Unit
Collected separately	0	kg
Collected with mixed construction waste	1	kg
Reuse	0	kg
Recycling	0,7	kg
Energy recovery	0	kg
Landfill	0,3	kg
Transport to waste treatment	100	km

6 CUT-OFF RULES AND ALLOCATION

Criteria for the exclusion of inputs and outputs (cut-off rules) in the LCA, information modules and any additional information are intended to support an efficient calculation procedure. They are not applied in order to hide data. Cut-off criteria, where applied, are described in Table 3.

Input flows are covered for the whole formula.

Table 3: Cut-off criteria

Process excluded from study	Cut-off criteria	Quantified contribution from process
A3: production (auxiliary materials)	Less than 10^{-5} kg/kg of finished product	Sensitivity study demonstrates a relative contribution lower than 0,5%

For the allocation procedure and principles consider the following table (Table 4):

Table 4: Allocation procedure and principles

Module	Allocation Principle
A1	All data are referred to 1 kg of product A1: electricity is allocated to the specific production line
A3	All data are referred to 1 kg of packaged product A3-wastes: all data are allocated to the specific production line

7 ENVIRONMENTAL PERFORMANCE AND INTERPRETATION



GWP

Climate change
GWPtotal - Global Warming Potential refers to the emission/presence of GHGs (greenhouse gases) in the atmosphere (mainly CO_2, N_2O, CH_4) which contribute to the increase in the temperature of the planet.
GWP-total considers:
- GWP-fossil
- GWP-biogenic
- GWP-luluc (land use and land use change)



ODP

Ozone Depletion
Ozone Depletion Potential refers to the degradation of the stratospheric layer of the ozone involved in blocking the UV component of sunrays. Depletion is due to particularly reactive components that originate from chlorofluorocarbon (CFC) or chlorofluoromethane (CFM).



AP

Acidification
Acidification Potential refers to the emission of specific acidifying substances (i.e. NOx, SOx) in the air. These substances decrease the pH of the rainfall with predictable damages to the ecosystem.



EP

Eutrophication
Eutrophication Potential refers to the nutrient enrichment, which determines unbalance in ecosystems and causes the death of the fauna and decreased biodiversity in flora.
It considers:
- EP-freshwater: acquatic freshwater
- EP-marine: acquatic marine
- EP-terrestrial



POCP

Photochemical ozone formation
The Photochemical Ozone Creation Potential is the ozone formation in low atmosphere. This is quite common in the cities where a great amount of pollutants (like VOC and NOx) are emitted every day (industrial emissions and vehicles). It is mainly diffused during the summertime.



ADP minerals&metals

Depletion of abiotic resources – minerals and metals
Abiotic Depletion Potential elements refers to the depletion of the mineral resources.



ADP-fossil

Depletion of abiotic resources – fossil fuel
Abiotic Depletion Potential fossil fuel refers to the depletion of the fossil fuel resources.



WDP

Water use
It expresses the potential deprivation of water, that consists in not having the water needs satisfied.

The following tables show the environmental impacts for the products considered according to the requirements of EN15804:2012+A2:2019/AC:2021. The Characterization Factors are based on EF 3.1 package. The results are referred to the declared unit (see § 4). The additional environmental indicators are not declared. The estimated impact results are only relative statements, which do not indicate the endpoints of the impact categories, exceeding threshold values, safety margins and/or risks.

We discourage the use of the outcomes from modules A1-A3 without considering the results obtained from modules C.

Mapegrout Tissotropico Zero

(1 kg of product in 25 kg multiply bag)

Table 5: Mapegrout Tissotropico Zero: Potential environmental impact – mandatory indicators according to EN 15804 referred to 1 kg of product in packaging.

Indicator	Unit	A1 – A3	A4	A5	C1	C2	C3	C4	D
GWP_{TOTAL}	(kg CO_2 eq.)	3,28E-01	6,64E-02	2,02E-02	1,94E-03	8,87E-03	1,96E-03	4,66E-03	-1,23E-02
GWP_{FOSSIL}	(kg CO_2 eq.)	3,40E-01	6,26E-02	6,66E-03	1,92E-03	8,37E-03	1,93E-03	4,62E-03	-1,22E-02
$GWP_{BIOGENIC}$	(kg CO_2 eq.)	-1,28E-02	2,79E-03	1,35E-02	1,73E-05	3,72E-04	6,56E-06	1,33E-05	-2,02E-06
GWP_{LULUC}	(kg CO_2 eq.)	3,11E-04	1,02E-03	6,47E-06	2,92E-07	1,37E-04	2,61E-05	2,77E-05	-2,07E-05
ODP	(kg CFC 11 eq.)	7,37E-04	8,06E-05	6,29E-06	3,72E-06	1,10E-05	9,67E-06	3,28E-05	-1,31E-05
AP	(mol H^+ eq.)	6,44E-09	8,98E-15	2,50E-14	4,36E-14	1,20E-15	3,49E-15	1,25E-14	-2,63E-14
$EP_{FRESHWATER}$	(kg P eq.)	2,71E-05	2,60E-07	8,71E-09	7,98E-09	3,48E-08	7,52E-09	1,05E-08	-9,38E-09
EP_{MARINE}	(kg N eq.)	6,91E-05	2,89E-05	2,02E-06	9,27E-07	3,97E-06	4,45E-06	8,45E-06	-5,53E-06
$EP_{TERRESTRIAL}$	(mol N eq.)	2,46E-03	3,44E-04	2,24E-05	9,71E-06	4,74E-05	4,92E-05	9,31E-05	-6,10E-05
POCP	(kg NMVOC eq.)	2,26E-04	8,05E-05	5,42E-06	2,45E-06	1,10E-05	1,23E-05	2,59E-05	-1,43E-05
$ADP_{MINERALS\&METALS}$*	(kg Sb eq.)	7,41E-02	5,31E-09	2,42E-10	3,60E-10	7,09E-10	2,03E-09	3,00E-10	-5,95E-10
ADP_{FOSSIL}*	(MJ)	2,71E00	8,03E-01	3,05E-02	4,04E-02	1,07E-01	3,62E-02	6,10E-02	-1,93E-01
WDP*	(m^3 world eq.)	3,52E-02	9,45E-04	7,83E-03	5,32E-04	1,26E-04	3,70E-04	5,29E-04	-2,12E-04

GWP_{TOTAL}: Global Warming Potential total; **GWP_{FOSSIL}**: Global Warming Potential fossil fuels; **$GWP_{BIOGENIC}$**: Global Warming Potential biogenic; **GWP_{LULUC}**: Global Warming Potential land use and land use change; **ODP**: Depletion Potential of the stratospheric Ozone layer; **AP**: Acidification Potential; **$EP_{FRESHWATER}$**: Eutrophication Potential, freshwater; **EP_{MARINE}**: Eutrophication Potential, marine; **$EP_{TERRESTRIAL}$**: Eutrophication Potential, terrestrial; **POCP**: Formation potential of tropospheric ozone; **$ADP_{MINERALS\&METALS}$**: Abiotic Depletion Potential for non-fossil resources; **ADP_{FOSSIL}**: Abiotic Depletion Potential for fossil resources; **WDP**: Water Deprivation Potential.

* The results of this environmental impact indicator shall be used with care as the uncertainties on these results are high or as there is a limited experienced with the indicator

Table 6: Mapegrout Tissotropico Zero: Potential environmental impact – additional mandatory and voluntary indicators referred to 1 kg of product in packaging.

Indicator	Unit	A1 – A3	A4	A5	C1	C2	C3	C4	D
GWP-GHG	(kg CO_2 eq.)	3,41E-01	6,38E-02	6,68E-03	1,94E-03	8,53E-03	1,97E-03	4,67E-03	-1,23E-02

GWP-GHG: This indicator accounts for all greenhouse gases except biogenic carbon dioxide uptake and emissions and biogenic carbon stored in the product. As such, the indicator is identical to GWP-total except that the CF for biogenic CO_2 is set to zero. This new indicator cannot be compared with the GWP-GHG of the EPD according to the old PCR 1.2 (and earlier versions).

Table 7: Mapegrout Tissotropico Zero: Use of resources referred to 1 kg of product in packaging.

Indicator	Unit	A1 – A3	A4	A5	C1	C2	C3	C4	D
PERE*	MJ	1,85E-01	6,92E-02	2,13E-01	2,92E-02	9,24E-03	4,06E-03	1,06E-02	-1,63E-02
PERM*	MJ	1,96E-01	0,00E00	-1,96E-01	0,00E00	0,00E00	-2,07E-04	0,00E00	0,00E00
PERT*	MJ	3,81E-01	6,92E-02	1,70E-02	2,92E-02	9,24E-03	3,86E-03	1,06E-02	-1,63E-02
PENRE*	MJ	2,75E00	8,03E-01	5,14E-02	4,04E-02	1,07E-01	4,64E-02	6,10E-02	-1,93E-01
PENRM*	MJ	3,71E-02	0,00E00	-2,10E-02	0,00E00	0,00E00	-1,02E-02	0,00E00	0,00E00
PENRT*	MJ	2,79E00	8,03E-01	3,05E-02	4,04E-02	1,07E-01	3,62E-02	6,10E-02	-1,93E-01
SM	kg	5,45E-02	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00
RSF	MJ	1,05E-01	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00
NRSF	MJ	3,22E-02	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00
FW	m^3	8,67E-04	7,71E-05	1,88E-04	2,23E-05	1,03E-05	1,08E-05	1,62E-05	-2,81E-05

PERE: Use of renewable primary energy excluding renewable primary energy resources used as raw materials; **PERM**: Use of renewable primary energy resources used as raw materials; **PERT**: Total use of renewable primary energy resources (primary energy and primary energy resources used as raw materials); **PENRE**: Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; **PENRM**: Use of non-renewable primary energy resources used as raw materials; **PENRT**: Total use of non-renewable primary energy resources (primary energy and primary energy resources used as raw materials); **SM**: Use of secondary material; **RSF**: Use of renewable secondary fuels; **NRSF**: Use of non-renewable secondary fuels; **FW**: Net use of fresh water.

*According to Annex 3 of PCR 1.3.4, the option B for the calculation of primary energy use indicators has been used.

Table 8 Mapegrout Tissotropico Zero: Waste production and output flows referred to 1 kg of product in packaging.

Indicator	Unit	A1 – A3	A4	A5	C1	C2	C3	C4	D
HWD	kg	1,72E-03	3,08E-11	3,34E-11	5,83E-11	4,11E-12	5,23E-12	1,52E-11	-3,45E-11
NHWD	kg	1,39E-03	1,31E-04	1,12E-02	3,33E-05	1,75E-05	9,94E-06	3,09E-01	-1,46E-02
RWD	kg	1,07E-05	1,46E-06	3,60E-06	6,45E-06	1,95E-07	4,55E-07	6,40E-07	-2,28E-06
Components for re-use	kg	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00
Materials for recycling	kg	2,20E-02	0,00E00	7,06E-03	0,00E00	0,00E00	7,21E-01	0,00E00	0,00E00
Materials for energy recovery	kg	0,00E00	0,00E00	4,07E-03	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00
Exported energy, electricity	MJ	0,00E00	0,00E00	5,72E-03	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00
Exported energy, thermal	MJ	0,00E00	0,00E00	1,07E-02	0,00E00	0,00E00	0,00E00	0,00E00	0,00E00

HWD: Hazardous waste disposed; **NHWD**: Non-Hazardous waste disposed; **RWD**: Radioactive waste disposed

Table 9: Mapegrout Tissotropico Zero: Information on biogenic carbon content at the factory gate referred to 1 kg of product in packaging.

Biogenic Carbon Content	Unit	Quantity
Biogenic carbon content in product	kg C	0,00E00
Biogenic carbon content in packaging	kg C	4,49E-03

More details about electrical mix used in this EPD, is shown below:

	Data source	GWP-GHG	Unit
Residual electricity grid mix (GR) – 2023	Ecoinvent 3.10	0,810	kg CO_2-eqv/kWh

8 DATA QUALITY

Table 10: Data quality

Dataset & Geographical reference	Database (source)	Temporary reference
A1; A3		
Inorganic Binder	EPD/Ecoprofile from supplier	2022
Organic Binder	Ecoinvent 3.10	2023
Filler	Sphera Database	2023
Additives	Ecoinvent 3.10 Sphera Database	2023
Residual electricity mix (GR)	Ecoinvent 3.10	2023
Packaging components (EU)	Sphera Database; Ecoinvent 3.10	2023
A2		
Truck, Euro 5, 27t payload (GLO)	Sphera Database	2023
Light train, gross tonne weight 500t / 363t payload (GLO)	Sphera Database	2023
Diesel for transport (EU)	Sphera Database	2020
Heavy Fuel Oil (EU)	Sphera Database	2020
Electricity grid mix (EU)	Sphera Database	2020
A4		
Truck, Euro 6, 27t payload (GLO)	Sphera Database	2023
Diesel for transport (EU)	Sphera Database	2020
A5		
Commercial waste in municipal waste incineration plant	Sphera Database	2023
Inert matter on landfill	Sphera Database	2023
Electricity grid mix (EU)	Sphera database	2020
C1-C4		
Truck (EURO 6 - 9,3 ton payload – GLO)	Sphera Database	2023
Electricity grid mix (EU)	Sphera Database	2020
Diesel for transport (EU)	Sphera Database	2020
Construction waste dumping (EU)	Sphera Database	2023
Construction waste treatment (EU)	Sphera Database	2023

All data included in table above refer to a period between 2020 and 2023; the most relevant ones are specific from supplier, while the others (i.e. transport and minor contribution dataset), come from European and global databases. All datasets are not more than 10 years old according to EN 15804 §6.3.8.2 “Data quality requirements”.

The Quality level concerning datasets used in the EPD can be considered as” very good” or “good” according to Annex E of the EN 15804 (current version).

Primary data concern the year 2023 and represent the whole annual production.

9 ADDITIONAL INFORMATION

9.1 CO_2 offset

Total CO_2 emissions measured throughout the entire life cycle of the product have been offset through the acquisition of certified carbon credits in support of forestry protection projects. More information available at www.mapei.com.



9.2 Biogenic carbon content

For **Mapegrout Tissotropico Zero** the biogenic carbon content in packaging at the factory gate referred to 1 kg of product with packaging is 4,49E-03 kgC/kg.

9.3 Disassembly

The finished product is potentially suitable for disassembly through selective demolition.

9.4 Recycled content

Product	Recycled material content
Mapegrout Tissotropico Zero	5,45%

9.5 VOC Emissions

Volatile Organic Compounds (VOC) special tests and evidence have been carried out on the two products, according to ISO 16000 parts 3, 6, 9 and 11 and EN 16516.

The product has been evaluated in emission chambers, in order to detect their VOC emissions after 3 and 28 days storage in the ventilated chambers, according to GEV (Gemeinschaft Emissionskontrollierte Verlegewerkstoffe, Klebstoffe und Bauprodukte e.V.) test method.

The following product meets the requirements for the emission class EMICODE® **EC1^{PLUS}**, as "very low emission", released by GEV:

Mapegrout Tissotropico Zero: license number - 16290

Next table describes the limits for the EMICODE® EC1^{PLUS} class:

Table 11: EC1^{PLUS} VOC limits

	3 days µg/m³	28 days µg/m³
TVOC (C6-C16)	≤ 750 µg/m³	≤ 60 µg/m³
TSVOC (C16-C22)		≤ 40 µg/m³
C1A-C1B substances	Total ≤ 10 µg/m³	Single substance ≤ 1 µg/m³
Formaldehyde/ acetaldehyde	≤ 50 µg/m³	
Sum of formaldehyde/acetaldehyde	≤ 50 ppb	
sum of non-assessable VOCs		≤ 40
R value		≤ 1

10 VERIFICATION AND REGISTRATION

The EPD owner has the sole ownership, liability, and responsibility for the EPD.

EPDs within the same product category but registered in different EPD programmes, or not compliant with EN 15804, may not be comparable. For two EPDs to be comparable, they must be based on the same PCR (including the same version number) or be based on fully-aligned PCRs or versions of PCRs; cover products with identical functions, technical performances and use (e.g. identical declared/functional units); have equivalent system boundaries and descriptions of data; apply equivalent data quality requirements, methods of data collection, and allocation methods; apply identical cut-off rules and impact assessment methods (including the same version of characterisation factors); have equivalent content declarations; and be valid at the time of comparison. For further information about comparability, see EN 15804 and ISO 14025.

CEN standard EN15804 served as the Core Product Category Rules (PCR)	
PCR:	PCR 2019:14 Construction products (EN 15804:A2), Version 1.3.4, 2024-04-30
PCR review was conducted by:	The Technical Committee of the International EPD® System. See www.environdec.com/TC for a list of members. Review chair: Claudia A. Peña, University of Concepción, Chile. The review panel may be contacted via the Secretariat www.environdec.com/contact.
Independent third-party verification of the declaration and data, according to ISO 14025:2006:	☒ EPD Process Certification ☐ EPD Verification
Third party verifier:	Certiquality S.r.l. Number of accreditations: 0013VV rev.000
Accredited or approved by:	Accredia
Procedure for follow-up of data during EPD validity involves third-party verifier	☒ Yes ☐ No

11 REFERENCES

- EN 15804: SUSTAINABILITY OF CONSTRUCTION WORKS - ENVIRONMENTAL PRODUCT DECLARATIONS - CORE RULES FOR THE PRODUCT CATEGORY OF CONSTRUCTION PRODUCTS
- EUROSTAT - TREATMENT OF WASTE-BY-WASTE CATEGORY, HAZARDOUSNESS AND WASTE MANAGEMENT OPERATIONS
- EUROPEAN DIRECTIVE 2008/98/EC
- GENERAL PROGRAMME INSTRUCTIONS OF THE INTERNATIONAL EPD® SYSTEM. VERSION 4.0
- ISO 14025 ENVIRONMENTAL LABELS AND DECLARATIONS - TYPE III ENVIRONMENTAL DECLARATIONS - PRINCIPLES AND PROCEDURES
- ISO 14044 ENVIRONMENTAL MANAGEMENT – LIFE CYCLE ASSESSMENT – REQUIREMENTS AND GUIDELINES
- PCR 2019:14 CONSTRUCTION PRODUCTS (EN 15804: A2); VERSION 1.3.4

CONTACT INFORMATION

EPD owner:	Mapei Hellas S.A. www.mapei.gr
LCA author:	Mapei SpA www.mapei.it; Environmental Sustainability Office
Programme operator:	The International EPD® System Address: EPD International AB Box 210 60 SE-100 31 Stockholm Sweden Website: www.environdec.com E-mail: info@environdec.com

HEAD OFFICE
MAPEI SpA
Via Cafiero, 22 - 20158 Milan
Tel. +39-02-37673.1
mapei.com
mapei@mapei.it